



Centre Drive and Lay-on rolls



Italian Leader Worldwide
EUROMAC
SLITTERS REWINDERS

Euromac Costruzioni Meccaniche S.r.l. - Strada Statale 31 n.6 - 15030 Villanova Monf. - Italia
TEL. +39 0142.483195 - FAX +39 0142.483611 - www.euromacslitters.com • euromac@euromacslitters.com



TB-6CM Centre Drive and Lay-on rolls

UNWIND - Separate Shaftless or shafted unwinder • Dancing roller for tension control • Pneumatic Brake or electric Motor • Automatic webguiding system.

SLITTING - Slitting system with

oscillating Razorblades and/or Shear-cut rotary blades • Knifeholders on shaft or linear bearing guides • Specific web path for Wrap-cut or Tangent-cut • Manual or semi-automatic or full automatic positioning of slitting blades.

WEB PATH - Overhead web path • Aluminum idler rollers • Driven main pull roll with own pressure roller or "S" wrap.

REWIND - Centre wind assisted

by lay-on rolls • Independent rewind stations driven by own a.c. brushless motor • Linear bearing guides for fast positioning of the rewind stations • Manual, motorised or full-automatic positioning of rewind arms • Easy roll offloading on manual or motorised trolleys.

AUTOMATION - PLC for all machine functions and controls • Touch screen digital operator panel • Modem for remote monitoring.



MAIN SPECIFICATION	Standard	Option
Maximum web widths	1.200 to 3.500 mm	(or Custom)
Maximum rewind diameter	600 to 1.800 mm	(or Custom)
Maximum unwind diameter	800 to 1.800 mm	(or Custom)
Webguide stroke	± 75 mm	(or Custom)
Core diameter	76, 152 mm	(or Custom)
Maximum working speed	500-1000 m/min	(or Custom)
Web tension range	Customised	
Rewind system	Centre and Lay-on rolls	(Gap rewind)
Slitting	Oscillating razors	(Shear)
Material	Monolayers (CPP, BOPP, BOPA, BOPP, PVC, PET), Laminates, Coextrusion films, Paper, Paper/PE, Metalised films. Aluminum laminates.	
Best Choice for	CPP, MCPP / BOPP, PET / Coated Paper	